



# DC TALENT-22

standing *ultra fast* charger



## DC TALENT-22 STANDING CHARGER PARAMETERS

The **DC Talent-22** electric car charger is primarily recommended for larger companies, office buildings, on the street, in the parking lot of hotels, shopping centers and gas stations. The charger is the best choice for charging via mobile application. The application is available for iOS and ANDROID based smartphones. Once registered in the app, public epcharger charging points are available.

### *Smart standing direct current ultra fast charger has:*

- CCS Combo 2 cable,
- OCPP 1.6 J communications,
- MID authentic consumption meter, surge arrester,
- MOD bus or GSM connection surface, which is suitable for any billing method and energy management,
- white/black powder-coated stainless metal housing,
- smart controller which can also handle power distribution,
- RFID reader,
- emergency button

### *Main features:*

- Charging power: 22kW
- Standard charging mode: RFID / QR code
- Protection IP54, mechanical strength IK10
- Physical dimensions of the charger: (W x H x D) 480 x 1650 x 700 mm, weight: 148 kg

### *Optionally available:*

- with CCS Combo 2 and/or ChaDeMo cable,
- it can be supplemented with a Type 2 alternating current connector socket or fixed cable,
- with individual decals

The charger can be installed also in locations which are qualified as „areas open to public traffic” where there would be the need of involving an external e-mobility service provider and make the charging equipment available for paid charging through application.



## DC TALENT-22 STANDING CHARGER PARAMETERS

### SUPPLY CONNECTIONS

3 PHASE 400V ~ 50 Hz

### POWER

1x22 kW

### AMPERAGE

3x32 A

### MECHANICAL PROTECTIONS

IP54  
IK10

### ELECTRICAL PROTECTIONS

6mA DC  
30mA DC  
Surge arrester

### COMMUNICATIONS

Ethernet  
GSM module  
OCPP 1.6 J

### CHARGE MODE

MODE 4 (EN/IEC 61851-1)

### CONNECTOR

CCS Combo 2



## Parameters

Width  
480 mm

Height  
1650 mm

Depth  
700 mm