

HT 11 – HT 22

Portable DC charger datasheet



Specifications

Type	HT 11	HT 22
Rated power	11 kW	22 kW
Input voltage range	3 x 400 V AC $\pm$ 10 % (50 Hz)	3 x 400 V AC $\pm$ 10 % (50 Hz)
Maximum input current	3x16 A (AC) (adj.)	3x32 A (AC) (adj.)
Output voltage	50 ...500 V DC	50 ... 500 V DC
Maximum output current (DC)	30 A	60 A
Connectors	CCS (Combo 2) or CHAdeMO	CCS (Combo 2) or CHAdeMO
Efficiency	95 %	95 %
Built-in protection	Short circuit, overvoltage, overload, overheating	Short circuit, overvoltage, overload, overheating
Operating temperature	-20 °C ... + 50 °C	-20 °C ... + 50 °C
Design	portable / wall-mounted	portable / wall-mounted
Protection	IP 44	IP 44
Weight	22 kg	33 kg
Dimensions	H:280 x W:530 x D:280 mm	H:360 x W:530 x D:280 mm

Elektro Profi Mobility Kft.

1148 Budapest, Fogarasi u. 2-6.

+ 36 30 719 81 27

www.epcharger.hu

mobility@elektroprofi.hu

